

Spray valve MKDD - S

*Vom Fachmann
• FROM EXPERTS • TO EXPERTS •
für den Fachmann*



schütze

The spray valves of series MKDD - S are specially designed for the application of glues and adhesives. Also other fluids as oils, release agents can be sprayed. They can be used for continuous or intermitted employments.

Short air channels within the valve body and the direct mounted 3/2 way-solenoid valve give this valve very fast and exact needle intermission cycles.

The fastening of this valve to a machine can be done via the 2 bores (thread M5). Optional clamps are available.

Different versions of air caps allows an optimal spray jet for each application.

- Available nozzle dimensions:
0,3/0,5/0,8/1,0/1,2/1,5/2,0 mm \varnothing
- Ratchet regulator for easy adjusting amount of fluid
- Solenoid valves in different tensions (24V/DC / 110V/AC / 220V/AC)
- Different nozzles and air caps for individual application requirements.



technical data:

material pressure	:max. 35 bar
control air pressure	:min. 5 – 6 bar
measurements	:132 x 22 x 81mm (incl. solenoid valve)
valve body	:stainless steel
nozzle + needle	:stainless steel
gaskets	:viton (other materials on request)

ALFRED SCHÜTZE Apparatebau GmbH
- Spraytechnology -
Hannoversche Str. 69-71, D-28309 Bremen;
P.O. Box 44 86 48, D-28286 Bremen-Germany
Tel. +49 (421) 43 51 00
Fax +49 (421) 4 35 10-43
www.schuetze-gmbh.de
info@schuetze-gmbh.de