



AIRLESS- spray guns

S 720/250 Standard

S 720/500 Universal

S 720/LV Extrusion

*Vom Fachmann
• FROM EXPERTS • TO EXPERTS •
für den Fachmann*



schütze

The AIRLESS-spray guns **S 720/250** and **S 720/500** are suitable to fit all standard AIRLESS-pumps. These spray guns are spraying liquids without atomizing air. They can be equipped with standard AIRLESS-nozzles or nozzle cleaning devices as "roto-clean" or the like.

The model **S 720/250** can be used for material pressures up to 250 bar.

The model **S 720/500** can be used for material pressures up to 500 bar. For less fatiguing handling the spray gun is equipped with a regulating unit to adjust the power of the needle return spring, efficiently to all adequate fluid pressures.

The spray gun **S 720/LV** is an extrusion gun (without atomizing the material). It is designed for bead pattern application of glues and other high viscosity fluids.

The following further advantages of AIRLESS-spray guns of series S 720 were realized:

- robust construction
- ergonomic design for comfortable handling
- long trigger for optimal leverage
- reliable seat unit for durable use under hardest conditions
- mechanics without any problems
- needle seat parts made from tungsten carbide

Safety measures:

- trigger lock
- strigger guard

Standard version:

- filter
- swivel 1/4"
- tool

DISTRIBUTOR IN BALTICS:

PAKARTE LLC
Phone+372 5656 9482
pakarte@pakarte.com
www.pakarte.com



S 720/LV



S 720

Technical data:

weight:	approx. 700 g
max. pressure:	S 720/250 = 250 bar
	S 720/500 = 500 bar
	S 720/LV = 50 bar

Technical alterations reserved.

ALFRED SCHÜTZE Apparatebau GmbH
- Spraytechnology -

Hannoversche Str. 69-71, D-28309 Bremen;

P.O. Box 44 86 48, D-28286 Bremen-Germany

Tel. +49 (421) 43 51 00

Fax +49 (421) 4 35 10-43

www.schuetze-gmbh.de

info@schuetze-gmbh.de

AIRLESS-spray guns
S 720/250 Standard
S 720/500 Universal



The AIRLESS-spray guns S 720/250 and S 720/ 500 are suitable to fit all standard AIRLESS-pumps. These spray guns are spraying fluids without atomizing air. They can be equipped with standard AIRLESS-nozzles or nozzle cleaning devices as "roto-clean" or the like.

The model S 720/250 can be used for material pressures up to 250 bar. The model S 720/500 can be used for material pressures up to 500 bar. For less fatiguing handling the spray gun is equipped with a regulating unit to adjust the power of the needle return spring, efficiently to all adequate fluid pressures.

The following further advantages of AIRLESS-spray guns of series S 720 were realized:

- robust construction
- ergonomic design for comfortable handling
- long trigger for optimal leverage
- reliable seat unit for durable use under hardest conditions
- mechanics without any problems
- needle seat parts made from tungsten carbide

Safety measures:

- trigger lock
- strigger guard

Standard version:

- filter
- swivel 1/4"
- tool

Technical data:

weight:		ca. 700 g
material pressure:		S 720/250 = max. 250 bar S 720/500 = max. 500 bar
gun body:		aluminium, anodized
needle seat:		tungsten carbide
needle:		ball point tungsten carbide

DISTRIBUTOR IN BALTICS:

PAKARTE LLC
Phone+372 5656 9482
pakarte@pakarte.com
www.pakarte.com

Alfred Schütze Apparatebau GmbH
Zeppelinstraße 2, 28844 Weyhe-Dreye

Tel.: 0421 / 4 35 10 - 0
Fax: 0421 / 4 35 10 - 43

Special designs on request.
Technical alterations reserved.
For further information please contact us.

www.schuetze-gmbh.de
info@schuetze-gmbh.de