



1
2

DISTRIBUTOR IN BALTICS:

PAKARTE LLC

Phone +372 5656 9482

pakarte@pakarte.com

www.pakarte.com

Blowguns of series

W5

*Vom Fachmann
• FROM EXPERTS • TO EXPERTS •
für den Fachmann*



schütze

Excellently suitable for blowing, dusting and cleaning of workpieces, casting- and pressforms, electric motors, carburetors, sparking-plugs, casings, typewriters, office machines and all further equipment.

Longer pipes available.
Standard air connection = nipple for quick coupler (other connections on request).
Further special designs on request.
Technical alterations reserved.

For further information please contact us.

Abb. W 5/P/50 with 50 mm pipe

also available with 100, 200 or 250 mm pipe

Abb. W 5/P/S with rebound guard

recommended by professional associations for industrial safety

Abb. W 5/P/T with turbo nozzle

The induction air gives approx. triple the air volume. Less air consumption reduces the costs of blow air.
Also reduced rebound and larger applications.

Abb. W 5/P/G with silencer nozzle

reduce the noise level.

Abb. W 5/G with rebound guard

recommended by professional associations for industrial safety

Available standard versions:

W 5/P/50 blowgun with 50 mm pipe

W 5/P/100 blowgun with 100 mm pipe

W 5/P/200 blowgun with 200 mm pipe

W 5/P/250 blowgun with 250 mm pipe (straight ahead or bended)

W 5/P/S blowgun with rebound guard and 50 mm pipe

W 5/P/F blowgun with flat nozzle and 100 mm pipe

W 5/P/T blowgun with turbo nozzle

W 5/P/G blowgun with silencer nozzle and 50 mm pipe

W 5/PB 212 blowgun with venturi nozzle, 18 mm Ø

W 5/PB 512 blowgun with venturi nozzle, 8 mm Ø

W 5/G blowgun with straight handle with 50 mm pipe



W 5/P/S



W 5/P/G

ALFRED SCHÜTZE Apparatebau GmbH
- Spraytechnology -
Hannoversche Str. 69-71, D-28309 Bremen
Postfach 44 86 48, D-28286 Bremen
Tel. +49 (421) 4 35 10-0
Fax +49 (421) 4 35 10-43
www.schuetze-gmbh.de
info@schuetze-gmbh.de

Blowguns of series W 5

2 2



Excellently suitable for blowing, dusting and cleaning of workpieces and all further equipment.

Longer pipes available.

Standard air connection = nipple for quick coupler (other connections on request). Further special designs on request. Technical alterations reserved.

For further information please contact us.

Abb. W 5/P/50 with 50 mm pipe
also available with 100, 200 or 250 mm pipe

Abb. W 5/P/S with rebound guard
recommended by professional associations for industrial safety

Abb. W 5/P/T with turbo nozzle
The induction air gives approx. triple the air volume. Less air consumption reduces the costs of blow air. Also reduced rebound and larger applications.

Abb. W 5/P/G with silencer nozzle
reduce the noise level.

Abb. W 5/G with rebound guard
recommended by professional associations for industrial safety

Available standard versions:

W 5/P/50	blowgun with 50 mm pipe
W 5/P/100	blowgun with 100 mm pipe
W 5/P/200	blowgun with 200 mm pipe
W5/P/250	blowgun with 250 mm pipe (straight ahead or bended)
W5/P/S	blowgun with rebound guard and 50 mm pipe
W 5/P/F	blowgun with flat nozzle and 100 mm pipe
W 5/P/T	blowgun with turbo nozzle
W 5/P/G	blowgun with silencer nozzle and 50 mm pipe
W 5/PB 212	blowgun with venturi nozzle, 18 mm ø
W 5/PB 512	blowgun with venturi nozzle, 8 mm ø
W 5/G	blowgun with straight handle with 50 mm pipe



DISTRIBUTOR IN BALTICS:
PAKARTE LLC
 Phone+372 5656 9482
 pakarte@pakarte.com
 www.pakarte.com